

12 French Drive, R.R.#5 Orangeville, Ontario Canada L9W 2Z2
Tel. (519) 942-8800 Toll Free (800) 252-5636 Fax (519) 942-4799

CHAIN LUBE 1000 HFG

Product Description

Applied Lubrication Technology Inc. Chain Lube 1000 HFG has been developed to meet the extreme lubrication demands of industry. It performs similarly to our Chain Lube 1000 HF but is able to lubricate effectively at temperatures up to 482°C (900°F), due to the utilization of ultrafine graphite particles rather than molybdenum disulfide as the dry film lubricant.

This product acts as a lubricant, penetrant and cleaner that reaches all links, pins, and moving parts of a conveyor chain. The Chain Lube 1000 HFG contains a unique blend of extreme pressure lubricating agents which greatly reduce chain wear and drive power consumption leading to increased chain life.

Other unique qualities of the Chain Lube 1000 HFG are its high corrosion protection, water-displacing and acid atmosphere resistance properties enabling this lubricant to be used in the most severe and demanding industrial applications.

The Chain Lube 1000 HFG is especially formulated to be applied by ALT's automated lubrication system.

Chain Lube 1000 HFG Technical Specifications

Appearance	Dark Grey/Black
Odor	Mild Petroleum
Base Viscosity (of the concentrate portion)	144 cSt@ 40°C (667 sus@104°F)
	14.5 cSt@ 100°C (75 sus@212°F)
VI (Viscosity Index)	100
Flash Point (PMCC)	105°C minimum (221°F)
Copper Corrosion (ASTM D 130)	1b

Product Applications

Although this product has been specifically developed for the lubrication of conveyor chains using a programmable automated application system, the Chain Lube 1000 HFG can also be used for the lubrication of many different mechanical systems such as; bearings, gears, sprockets, hinges, firearms, linkages, threads, slides, cables, locking mechanisms, and more.

Product Packaging

Chain Lube 1000 HFG is available in 20 liter pails , 200 liter drums, and 1200 liter returnable tote bin quantities.

All reasonable care has been taken to ensure that the information contained in this document is accurate as of the date of printing. However, such information may be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Applied Lubrication Technology Inc. products and must be consulted for appropriate storage, safe handling and disposal information of the product.