

12 French Drive, R.R.#5 Orangeville, Ontario Canada L9W 2Z2
Tel. (519) 942-8800 Toll Free (800) 252-5636 Fax (519) 942-4799

CHAIN LUBE FCL-330

Product Description

Applied Lubrication Technology Inc. Chain Lube FCL-330 was specifically developed to meet the extreme lubrication demands of Heat Treatment Furnace Chains which reach temperatures beyond the capabilities of even the best, non solid containing, synthetic lubricants. FCL-330 base stocks were carefully selected to satisfy film strength requirements, the need to effectively penetrate into the hot chains, and the ability to break down residue that is present from previously utilized lubricants. These base stocks not only penetrate and lubricate but also deliver the highly stable wear and friction reducing dispersion of ultrafine graphite particles to the chains wear points. This graphite coating provides boundary lubrication at temperatures up to 482°C (900°F).

The FCL-330 base stocks and additives are all Copper and Zinc free by design in order to comply with requirements of specific Heat Treatment Processes. Chain Lube FCL-330 is ideally applied by the ALT automatic lubrication system.

Other advantages are as follows:

- Eliminates galling, seizing, stick-slip, and press-fit distortion
- Reduces break-in time for new equipment
- Prevents fretting
- Protects against Corrosion

Some of the important physical properties of this product are provided in the table below.

Chain Lube FCL-330 Technical Specifications

Appearance	Black
Viscosity	115 cSt@ 40°C (542 sus@104°F)
Flash Point	>250°C (482°F), COC
Operating Temperatures	Up to 900°F

Product Applications

This higher viscosity lubricant has been specifically developed for the lubrication of Heat Treatment Furnace Chains and other chain applications that are subject to increased temperatures.

Product Packaging

Chain Lube FCL-330 is available in 20 liter Plastic Pails, 200 liter drums, and 1200 liter returnable tote bin quantities.

All reasonable care has been taken to ensure that the information contained in this document is accurate as of the date of printing. However, such information may be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Applied Lubrication Technology Inc. products and must be consulted for appropriate storage, safe handling and disposal information of the product.