

12 French Drive, R.R.#5 Orangeville, Ontario Canada L9W 2Z2
Tel. (519) 942-8800 Toll Free (800) 252-5636 Fax (519) 942-4799

CHAIN LUBE FG-VG3

Product Description

Applied Lubrication Technology's food grade Chain Lube FG-VG3, is a non-molybdenum disulfide based synthetic lubricant containing high purity synthetic hydrocarbons. While competitor's lubricants will have degraded, Chain Lube FG-VG3 will remain as a liquid for longer periods of time, thereby reducing consumption. This lubricant also softens carbon residue that may have been left from previous lubricants used. It's wetting and penetrating ability loosens barrels and links which have heavy deposits and no longer spin or move freely. The temperature ranges for this lube range from ambient up to 550°F. Chain Lube FG-VG3 is NSF H1 food grade approved and CFIA (Canadian Food Inspection Agency) listed and is a heavier version of the FG-VG1, which typically enables application frequency to be decreased.

Chain Lube FG-VG3 is specially formulated to be applied by ALT's automated lubrication system.

Chain Lube FG-VG3 Technical Specifications

Appearance	Clear / Light Amber
Odor	Mild
Viscosity	15 cSt @ 40°C
Flash Point (TCC)	84°C (183°F)
Copper Corrosion (ASTM D 130)	11b
Falex Test Load Lbs.	+1800
Specific Gravity @ 15.6°C (g/ml.)	0.8148

Product Applications

Chain Lube FG-VG3 has been specifically developed for the lubrication of conveyor chains where NSF H1 Food Grade &/or CFIA Lubricants are required, however, its chemical composition makes it suitable for many other applications.

Product Packaging

Chain Lube FG-VG3 is available in 20 liter pails and 200 liter drums.

All reasonable care has been taken to ensure that the information contained in this document is accurate as of the date of printing. However, such information may be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Applied Lubrication Technology Inc. products and must be consulted for appropriate storage, safe handling and disposal information of the product.