

12 French Drive, R.R.#5 Orangeville, Ontario Canada L9W 2Z2
Tel. (519) 942-8800 Toll Free (800) 252-5636 Fax (519) 942-4799

CHAIN LUBE PCL-46

Product Description

Applied Lubrication Technology's Chain Lube PCL-46, is specifically formulated for use as a Pin Chain Lubricant where high operating speeds and temperatures are the norm. Chain Lube PCL-46 is a blend of carefully selected, high temperature stable synthetic ester, a propriety lubricity additive package, and extremely clean burning and temperature stable base stocks. It is a long lasting lubricant at temperatures up to 550°F, leaving very little varnish or carbon residue. While competitor's lubricants will have degraded and possibly deposited sticky residue, Chain Lube PCL-46 will remain as a liquid for longer periods of time, thereby reducing consumption, and will also soften carbon residue left from previously utilized lubricants. PCL-46 has been formulated to provide superior wetting and penetrating capability (over our competitors similar products), enabling it to better loosen barrels and links which have heavy deposits on them and no longer move freely.

Chain Lube PCL-46 Technical Specifications

| | |
|---|---------------|
| Appearance | Dark Amber |
| Odor | Mild |
| Viscosity | 46 cSt @ 40°C |
| Viscosity Index | 138 |
| Flash Point (COC) ASTM D92 | 251°C (484°F) |
| Four Ball Wear Scar, 1hr, 1800 rpm, 40Kg, 75°C (167°F) | 0.389mm |
| Evaporation Loss per ASTM D 2595 204 °C for 6.5hours | 5.19% |

Product Applications

Although specifically formulated as a high performance Pin Chain Lubricant ALT PCL-46 can also be used for the lubrication of many different mechanical systems such as; bearings, gears, sprockets, hinges, firearms, linkages, threads, slides, cables, locking mechanisms and more.

Product Packaging

Chain Lube PCL-46 is available in 20 liter pails, 200 liter drums, and 1200 liter tote bin quantities.

All reasonable care has been taken to ensure that the information contained in this document is accurate as of the date of printing. However, such information may be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Applied Lubrication Technology Inc. products and must be consulted for appropriate storage, safe handling and disposal information of the product.